



HEXOL 2T ECO

MIX OIL

PRODUCT DESCRIPTION

HEXOL 2T ECO is produced from highly refined mineral base oils with a low ash content, specially formulated with dispersants, depressants, anti-wear, anti-corrosion, anti-oxidant additives.

Recommended all year round in mixed lubrication engines or in fuel injection engines with air-cooling system.

PERFORMANCE FEATURES

- meets API TA standard requirements;
- Ideal lubrication is ensured at a 1:50 mixing ratio or at the mixing ratio specified by the engine's manufacturer;
- Provides lubrication and protection, avoiding spark plugs fouling, exhaust cover windows and peeling rings, keeping clean the plunger and lowering the combustion chamber deposits;
- Higher proportion of oil than the recommended one can generate a premature wear of the engine increasing pollution;
- Used in recommended proportions controls varnish, sludge and ash deposits and reduces smoke emission.

APPLICATION

- Recommended for two-stroke gasoline engines, motorbike engines, gardening equipments, chain saws and any other equipment where the manufacturer recommends this type of oil.

PROPERTIES

Viscosity Grade SAE	20
Density at 15°C [kg/m ³]	850 – 880
Kinematic Viscosity at 40°C [mm ² /s]	32-78
Flash Point [°C]min	105
Pour Point [°C]max	-25
Colour	green

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input checked="" type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input checked="" type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L

HEXOL INTERNATIONAL LTD