HEXOL INTERNATIONAL LTD



TECHNICAL DATA SHEET

HEXOL MOTO&GARDEN 2T API TC

MIX OIL

PRODUCT DESCRIPTION

HEXOL MOTO&GARDEN 2T API TC is a high quality mix oil, produced from highly refined mineral base oils with a low ash content, specially formulated with dispersants, depressants, anti-wear, anti-corrosion, anti-oxidant additives.

Recommended all year round in mixed lubrication engines or in fuel injection engines with air-cooling system.

PERFORMANCE FEATURES

- meets API TC; JASO FD(LO); ISO-L-EGD standards requirements;
- olso meets the requirements of the most important gardening equipment producers, as: MTD, Briggs&Stratton, Honda, Tecumseh, John Deere and others;
- Ideal lubrication is ensured at a 1:50 mixing ratio or at the mixing ratio specified by the engine's manufacturer;
- Provides lubrication and protection, avoiding spark plugs fouling, exhaust cover windows and peeling rings, keeping clean the plunger and lowering the combustion chamber deposits;
- Higher proportion of oil than the recommended one can generate a premature wear of the engine increasing pollution;
- Used in recommended proportions controls varnish, sludge and ash deposits and reduces smoke emission.

APPLICATION

- Recommended for two-stroke gasoline engines equipping gardening equipments, motorbikes, motor boats, ATV and any other equipment where the manufacturer reccomands this type of oil.

PROPERTIES

Viscosity Grade SAE	20
Density at 15°C [kg/m³]	850 - 880
Kinematic Viscosity at 40°C [mm²/s]	32-78
Kinematic Viscosity at 100°C [mm²/s]	5.6-9.3
Flash Point [°C]min	150
Pour Point [°C]max	-25
Colour	red

PACKAGING

0.4Kg	□ 1Kg	4Kg	□ 15Kg	☐ 180Kg		
0.23L	0.45L	0.5L		0.9L	1L	☐ 3L
4L		□ 10L	≥ 20L	☐ 60L		