



## HEXOL AR 165

INDUSTRIAL OIL, CORROSION PROTECTION OIL

### PRODUCT DESCRIPTION

Hexol AR 165 is specially formulated from highly refined mineral oil containing anti-corrosion additives. Hexol AR 165 provides corrosion protection for steel during processing and storage, by forming a protective film on the treated surface.

### PERFORMANCE FEATURES

- excellent water repellent properties;
- easily removable.

### APPLICATION

- Hexol AR 165 is used to protect against the corrosion of steel elements during processing and storage;
- Application on the surface can be done mainly by spraying, but it can also be applied by spreading or brushing;
- The product can be easily removed from the surface, using organic solvents or water soluble cleaning agents.

### PROPERTIES

	AR 165
Viscosity grade ISO	32
Density at 15°C [kg/m <sup>3</sup> ]	880
Kinematic Viscosity at 40°C [mm <sup>2</sup> /s]	28.8-35.2
Flash Point [°C ]min	215
Pour Point [°C ]max	-15

### PACKAGING

- |                                |                                |   |   |   |  |   |
|--------------------------------|--------------------------------|---|---|---|--|---|
| <input type="checkbox"/> 0.4Kg | <input type="checkbox"/> 1Kg   | <input type="checkbox"/> 4Kg            | <input type="checkbox"/> 15Kg           | <input type="checkbox"/> 180Kg          |  |   |
| <input type="checkbox"/> 0.23L | <input type="checkbox"/> 0.45L | <input type="checkbox"/> 0.5L           | <input type="checkbox"/> 0.6L           | <input type="checkbox"/> 0.9L           | <input type="checkbox"/> 1L              | <input type="checkbox"/> 3L               |
| <input type="checkbox"/> 4L    | <input type="checkbox"/> 5L    | <input checked="" type="checkbox"/> 10L | <input checked="" type="checkbox"/> 20L | <input checked="" type="checkbox"/> 60L | <input checked="" type="checkbox"/> 208L | <input checked="" type="checkbox"/> 1000L |

