# HEXOL INTERNATIONAL LTD



# TECHNICAL DATA SHEET

## **HEXOL AFT DEXRON II**

GEAR OIL

### PRODUCT DESCRIPTION

HEXOL ATF DEXRON II is outstanding quality transmission oil, for use in semi-automatic and automatic transmissions installations equipping industrial equipment and vehicles, in power steering systems. Hexol ATF DEXRON II is formulated from mineral base oils combined with specific additives, recommended for use throughout the year to automatic transmission systems equipping last generation industrial equipment and vehicles, or any transmissions where specified using a such oil.

### PERFORMANCE FEATURES

- meets requirements according to GM Dexron IID, Ford Mercon, Allison C4, MAN 339 Typ V1-Z1, CATERPILLAR TO2, Voith H55.6335, ZF TE-ML 04D, ZF TE-ML 09/ 11B/ 14A/ 17C and other types of vehicles whose manufacturers recommend that classification;
- ensures a long life of components subject to wear;
- has good thermal stability;
- excellent oxidative stability, providing protection against corrosion or sediment deposits.

### **APPLICATION**

- recommended for all semi-automatic and automatic transmission systems equipping last generation of industrial equipment and vehicles requiring an oil corresponding to GM Dexron IID, MB 236.1, Ford Mercon, Allison C4;
- recommended for hydraulic systems requiring anti-wear oils with good fluidity even at low temperatures.

### **PROPERTIES**

Viscosity Grade SAE	20
Density at 15°C [kg/m³]	850 - 870
Kinematic Viscosity at 40°C [mm²/s]	30 - 46
Kinematic Viscosity at 100°C [mm²/s]	6 – 8
Viscosity Index, min	150
Flash Point [°C]min	200
Pour Point [°C] max	-36
Brookfield viscosity at -40°C [mPa.s] max	50000
Colour	red

### **PACKAGING**

0.4Kg	☐ 1Kg	4Kg	☐ 15Kg	☐ 180Kg		
0.23L	0.45L	0.5L	0.6L	0.9L	□ 1L	3L
4L				☐ 60L		