



## HEXOL CA 3 PREMIUM

GREASE

### PRODUCT DESCRIPTION

HEXOL CA 3 PREMIUM, is a calcium-base lubricating grease, generally used water resistant product. Suitable for lubricating points where among water resistance the sealing ability is required, loads are moderate and the operating temperature does not exceed +60°C. Especially suitable for lubrication of pivots, joints in agriculture and industry where dust is typical.

### PERFORMANCE FEATURES

- meets ISO 6743-9: L-XBAHA 3; DIN 51502; K3C-20; NLGI 3 specifications;
- excellent dynamic water resistance;
- good lubricating characteristic;
- good sealing-ability;
- long-lasting corrosion protection.

### APPLICATION

Suitable for lubricating points where among water resistance and sealing ability is required and the operating temperature does not exceed +60°C.

### PROPERTIES

Appearance	red, homogeneous
Dropping point [°C]	95
Penetration after 60 strokes at 25 °C [0,1 mm]	230
Corrosion at 60 °C/ 3 h (copper) [grade]	1b
EMCOR test, distilled water [grade]	1
Dynamic water - resistance at 79 °C [mass %]	3

### PACKAGING

<input checked="" type="checkbox"/> 0.4Kg	<input checked="" type="checkbox"/> 1Kg	<input checked="" type="checkbox"/> 4Kg	<input checked="" type="checkbox"/> 15Kg	<input checked="" type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input type="checkbox"/> 10L	<input type="checkbox"/> 20L	<input type="checkbox"/> 60L	<input type="checkbox"/> 208L	<input type="checkbox"/> 1000L