



HEXOL STANDARD CHAIN OIL

CHAIN SAW OIL

PRODUCT DESCRIPTION

Hexol Standard Chain Oil is recommended for lubricating open gears, chains, chainsaws, axels, bearings etc. It has in its composition anti-wear additives, anticorrosion additives and tackifier agents that improve adhesion, decreasing fuel and lubricant consumption.

PERFORMANCE FEATURES

- reduced friction and wear;
- economic lubricant consumption;
- excellent tackiness.

APPLICATION

- recommended for lubricating open gears, chains, chainsaws, axels, bearings etc;
- recommended for use in all seasons.

PROPERTIES

Density at 15°C [kg/m ³]	870 – 890
Kinematic Viscosity at 40°C [mm ² /s]	68-100
Flash Point [°C]min	195
Pour Point [°C]max	-20

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input checked="" type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input checked="" type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L

HEXOL INTERNATIONAL LTD

HEXOL LUBE SRL

Oradea Metropolitan Area • 417166 Paleu, 1A Ardealului st, Bihor • Romania
Tel +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com

REV.
2019