



HEXOL DOT 4 BRAKE FLUID

PRODUCT DESCRIPTION

Hexol DOT 4 brake fluid is a modern synthetic brake fluid based on glycols and polyglycols, made with oxidation inhibitor, anti-corrosion and anti-foaming additives. Its outstanding humidity absorption ability prevents formation of ice crystals at low temperatures and vapour bubbles at high temperatures in the fluid. Its anti-corrosion additives ensure high-level protection for the internal metal parts (cast iron, copper, zinc, cadmium, aluminium) of the brake system. Hexol DOT 4 brake fluid provides perfect lubrication for the internal parts of the brake system.

PERFORMANCE FEATURES

- Meets requirements of the following standards, DOT 4, FMVSS 116, CMVSS 116, SAE J1703/J1704, ISO 4925 Class 4;
- Synthetic brake fluid ;
- High boiling point;
- Excellent compatibility with rubbers, elastomers and metals;
- Very good lubricating properties.

APPLICATION

Hexol DOT 4 brake fluid may be used for hydraulic brake systems in passenger cars, utility vehicles and construction equipment where operating manuals demand brake fluids with a boiling point at 260°C and DOT 4 quality.

Hexol DOT 4 can be mixed with any other synthetic brake fluids of the same specifications. DO NOT mix with mineral oil based brake fluids.

PROPERTIES

Density at 20°C [kg/m ³]	1030 – 1080
Boiling Point [°C]min	230
Wet boiling Point [°C]max	155
Ph	8 – 9
Colour	light yellow

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input checked="" type="checkbox"/> 0.23L	<input checked="" type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input checked="" type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input type="checkbox"/> 10L	<input type="checkbox"/> 20L	<input type="checkbox"/> 60L	<input type="checkbox"/> 208L	<input type="checkbox"/> 1000L