



## HEXOL BK 22 - BK 32

INDUSTRIAL OIL, MOLD RELEASE OIL

### PRODUCT DESCRIPTION

Hexol BK 22 and 32 are highly refined mineral oils containing release improver and anticorrosion additives. They prevent concrete from adhering to the mold, thus making the demolding and cleaning of mold easier. The product provides temporary corrosion protection for steel molds between two processings.

### PERFORMANCE FEATURES

- easy demolding;
- clean surfaces.

### APPLICATION

- Hexol BK 22 - BK 32 are used for the lubrication of steel molds in the production of concrete elements;
- Application on the surface can be done by spreading, brushing and swabbing.

### PROPERTIES

	BK 22	BK 32
Density at 15°C [kg/m <sup>3</sup> ]	850 - 870	850 - 875
Kinematic Viscosity at 40°C [mm <sup>2</sup> /s]	22	32
Flash Point [°C ]min	195	200
Pour Point [°C ]max	-15	-15

### PACKAGING

- |                                |                                |   |   |   |  |   |
|--------------------------------|--------------------------------|---|---|---|--|---|
| <input type="checkbox"/> 0.4Kg | <input type="checkbox"/> 1Kg   | <input type="checkbox"/> 4Kg            | <input type="checkbox"/> 15Kg           | <input type="checkbox"/> 180Kg          |  |   |
| <input type="checkbox"/> 0.23L | <input type="checkbox"/> 0.45L | <input type="checkbox"/> 0.5L           | <input type="checkbox"/> 0.6L           | <input type="checkbox"/> 0.9L           | <input type="checkbox"/> 1L              | <input type="checkbox"/> 3L               |
| <input type="checkbox"/> 4L    | <input type="checkbox"/> 5L    | <input checked="" type="checkbox"/> 10L | <input checked="" type="checkbox"/> 20L | <input checked="" type="checkbox"/> 60L | <input checked="" type="checkbox"/> 208L | <input checked="" type="checkbox"/> 1000L |