



## HEXOL GA 32 – GA46 – GA 68

SLIDEWAY OIL

### PRODUCT DESCRIPTION

HEXOL GA 32 – GA 46 – GA 68 are specially formulated from highly refined mineral oils and a specific additive package (antioxidant, antiwear and corrosion inhibitor). It provides excellent lubrication in many industrial applications as slideway oil.

### PERFORMANCE FEATURES

- meets requirements according to ISO VG 32, 46, 68;
- good antiwear and EP properties;
- good oxidative stability, providing protection against corrosion or sediment deposits.

### APPLICATION

HEXOL GA 32 – GA 46 – GA 68 are applicable for lubricating slideways, machine tools, bearings or other industrial equipment with medium load gears.

### PROPERTIES

Viscosity Grade ISO	32	46	68
Density at 15°C [kg/m <sup>3</sup> ]	890	895	895
Kinematic Viscosity at 40°C [mm <sup>2</sup> /s]	28.8-35.2	41.4-50.6	61.2-74.8
Flash Point [°C ]min	215	215	215
Pour Point [°C ]max	-15	-15	-10

### PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L



## HEXOL GA 100 – GA 220

SLIDEWAY OIL

### PRODUCT DESCRIPTION

HEXOL GA 100 – GA 220 are specially formulated from highly refined mineral oils and a specific additive package (antioxidant, antiwear and corrosion inhibitor). It provides excellent lubrication in many industrial applications as slideway oil.

### PERFORMANCE FEATURES

- meets requirements according to ISO VG 100, 220;
- good antiwear and EP properties;
- good oxidative stability, providing protection against corrosion or sediment deposits.

### APPLICATION

HEXOL GA 100 – GA 220 are applicable for lubricating slideways, machine tools, bearings or other industrial equipment with medium load gears.

### PROPERTIES

Viscosity Grade ISO	100	220
Density at 15°C [kg/m <sup>3</sup> ]	900	900
Kinematic Viscosity at 40°C [mm <sup>2</sup> /s]	90-110	200-240
Flash Point [°C] min	215	220
Pour Point [°C] max	-10	-10

### PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L