



HEXOL K 22 – K 32 – K 46

COMPRESSOR OIL

PRODUCT DESCRIPTION

HEXOL K series is a standard quality compressor oil specially formulated to be used in lubricating cylinders and drive mechanisms of piston type compressors, where the manufacturer recommends an oil with these characteristics. Hexol K is produced from highly refined mineral base oils.

PERFORMANCE FEATURES

- meets DIN 51506 – VB, DIN 51517-1;
- good thermal stability;
- low foaming, rapid air separation;
- compatible with other conventional compressor oils.

APPLICATION

- are highly recommended for lubricating single- or multi-stage , fix or mobile piston compressors;
- can be used as hydraulic fluid where a standard quality oil is recommended.

PROPERTIES

Viscosity Grade ISO	22	32	46
Density at 15°C [kg/m ³]	850 - 870	850 - 875	850 - 875
Kinematic Viscosity at 40°C [mm ² /s]	19.8-24.2	28.8-35.2	41.4-50.6
Flash Point [°C]min	215	220	225
Pour Point [°C]max	-15	-15	-15

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input checked="" type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L