



## HEXOL LA 22 – LA 32 – LA 46

SLIDING BEARINGS OIL

### PRODUCT DESCRIPTION

Hexol LA 22 - LA 32 - LA 46 are obtained from highly refined mineral oil with a well-balanced additive system such as: anti-corrosion, anti-wear, anti-oxidant and anti-foam additives. The products can be used as lubricating oil for sliding bearings or in other applications where a high quality lubricating oil is recommended.

### PERFORMANCE FEATURES

- meets DIN 51517-2 (CL). DIN 51524-1 (HL);
- excellent wear protection;
- long-term oxidation stability;
- low foaming, rapid air separation.

### APPLICATION

Hexol LA 22 - LA 32 - LA 46 are used for the lubrication of sliding bearings at low speeds and loadings. This series can be used as general purpose lubricating oil or hydraulic oil, in applications where a high quality oil is recommended.

### PROPERTIES

Viscosity gradea ISO	22	32	46
Density at 15°C [kg/m <sup>3</sup> ]	850-870	850-875	850-875
Kinematic Viscosity at 40°C [mm <sup>2</sup> /s]	19.8-24.2	28.8-35.2	41.4-50.6
Flash Point [°C ]min	210	215	220
Pour Point [°C ]max	-15	-15	-15

### PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L