



## HEXOL LI EP 00 CENTRAL

GREASE

### PRODUCT DESCRIPTION

HEXOL LI EP 00 CENTRAL is a semi-liquid lithium grease, high quality, waterproof, intended for use in a wide range of industrial and automotive applications. Provides lubrication performance under severe temperatures, working ideally in temperatures situated from -30°C to +100°C. Formulated from high quality mineral oil and lithium soap, withstanding extreme pressure, containing EP, corrosion, anti-wear, antioxidant additives.

### PERFORMANCE FEATURES

- meets ISO 6473-9: L-XCCEB 00, DIN 51502: KP00G-30, NLGI-00 specifications;
- water resistance;
- low friction;
- very good corrosion protection;
- excellent mechanical stability.

### APPLICATION

- especially recommended for centralized lubrication systems in transport vehicles and auxiliary equipment operated outdoors with long pipelines.

### PROPERTIES

Base Oil Viscosity at 40°C [mm <sup>2</sup> /s]	120
Dropping point °C	165
Penetration after 60 strokes at 25°C (0.1mm)	415
Four ball test, weld load (N)	3150
Four ball test 60 sec/1000N wear diameter (mm)	0.60
Copper corrosion (100°C, 24h) [grade]	1b
EMCOR test [grade]	1
Dynamic water – resistance at 79°C [% (m/m)]	10
Flow pressure at -30°C [mbar]	1200

### PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input checked="" type="checkbox"/> 4Kg	<input checked="" type="checkbox"/> 15Kg	<input checked="" type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input type="checkbox"/> 10L	<input type="checkbox"/> 20L	<input type="checkbox"/> 60L	<input type="checkbox"/> 208L	<input type="checkbox"/> 1000L