



HEXOL SYNLINER SUPERDIESEL 10W40

MOTOR OIL

PRODUCT DESCRIPTION

Hexol Synliner Superdiesel 10W40 is specially formulated for light and heavy duty diesel applications recommended for use in naturally aspirated or super-charged diesel truck engines, construction, farm equipments and passenger cars, equipped with Euro III, Euro IV, or Euro V- without DPF. Hexol Synliner Superdiesel 10W-40 engine oil is formulated using highly refined mineral and synthetic base oils, with well-balanced additive system (high level of detergent/ dispersant, anti-wear, antioxidant, anticorrosive and antifoam, acid neutralising and flow properties modifier).

PERFORMANCE FEATURES

- exceeds API Service CI-4/SL, ACEA E7-08, ACEA A3/B4-04 requirements;
- meets standards imposed by auto makers such MB- 228.3/ 229.1/ 235.28, MAN M 3275-1, Volvo VDS-3, Renault RLD-2, DAF HP-1/HP-2, Deutz DQC III-10, MTU Type 2, Caterpillar ECF-1 ECF-2, Cummins CES 20076/CES 20077, CES 20078, Mack EOM-Plus, ZF.TE-ML7C, Allison C-4;
- protects the engine from corrosion, wear, rust, deposits and varnish;
- reduces high temperature oxidation minimizing oil thickening;
- excellent high temperature stability;
- low valve train, ring and liner wear.

APPLICATION

- suitable for Euro III, Euro IV, and Euro V – without DPF- light and heavy duty diesel engines, equipping trucks, construction, farm equipments and passenger cars, operating under severe conditions, where the manufacturer recommends an oil with API service CI-4/SL or lower performance;
- the drain interval will be according to the engine manufacturer indication.

PROPERTIES

Viscosity Grade SAE	10W40
API Service	CI-4/SL
Density at 15°C [kg/m ³]	850 – 880
Kinematic Viscosity at 100°C [mm ² /s]	12.5-16.3
Viscosity Index, min	160
Flash Point [°C]min	210
Pour Point [°C]max	-39

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg	<input checked="" type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L
<input checked="" type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L		

HEXOL INTERNATIONAL LTD

HEXOL LUBE SRL

Oradea Metropolitan Area • 417166 Paleu, 1A Ardealului st, Bihor • Romania
Tel +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com

REV.
2019