



## HEXOL SYNLINER TORSION 75W80

GEAR OIL

### PRODUCT DESCRIPTION

Hexol Synline Torsion 75W80 is an extra high performance, synthetic blend, multigrade automotive gear oil. It is produced from high quality synthetic and highly refined hydro cracked base oils using a complex additive system, ensuring excellent wear protection. Recommended for usage in the most advanced automotive manual gearboxes and other hypoid gears.

### PERFORMANCE FEATURES

- Exceeds API service GL-5 and GL-4 requirements;
- Meets requirements of the standards imposed by automakers such Tatra TDS 80/32, MIL-L-2105D, ZF TE-ML 07A, ZF TE-ML 17B;
- Optimal lubrication over a wide temperature range (-40°C up to 50°C);
- Excellent wear protection that extends gear lifecycle;
- Extremely long oil lifetime;
- Excellent thermal stability and oxidation stability;
- This oil maintains its properties for up to 5 years when in its original container, sealed, and stored away from any heat source and direct sunlight (storage temperature max. 40°C).

### APPLICATION

- It is suitable for gearboxes, steering devices, axle housings and universal joints equipped on passenger cars, vans, light and heavy commercial vehicles, construction and agricultural machinery, where the manufacturer recommends an oil with the above listed parameters;
- Qualified to be used as a lubricant in other hypoid gears in industrial equipment;
- It has an extremely long drain interval, providing even lifetime lubrication, depending on the gearbox manufacturer's recommendation.

### PROPERTIES

Viscosity Grade SAE	75W80
Density at 15°C [kg/m <sup>3</sup> ]	850 – 880
Kinematic Viscosity at 100°C [mm <sup>2</sup> /s]	7-11
Viscosity Index, min	150
Flash Point [°C] min	215
Pour Point [°C] max	-40

### PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg	<input checked="" type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L
<input type="checkbox"/> 4L	<input checked="" type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L		