# **HEXOL INTERNATIONAL LTD**



# TECHNICAL DATA SHEET

## **HEXOL SPRINT 15W40**

MOTOR OIL

### PRODUCT DESCRIPTION

Hexol Sprint 15W40 is a multigrade engine oil, produced from highly refined mineral base oils with use of a complex additive system (detergent, dispersant, antioxidant, anti-wear, anticorrosive and antifoam agents, pour point depressant, and viscosity modifier). It is ideal for naturally aspirated and turbocharged engines of gasoline, diesel LPG powered passenger cars and light commercial vehicles, where the manufacturer recomands this type of oil.

### PERFORMANCE FEATURES

- exceeds API service SF/CC; MIL-L-46152 B;
- meets passenger car and light truck manufacturers warranty requirements;
- lubricates, cools and protects engines that operate at high temperatures;
- protects the engine from corrosion, wear, rust, deposits and varnish;
- reduces high temperature oxidation.

### **APPLICATION**

- passenger cars and trucks equiped with gasoline, diesel or LPG engines where the producer recomands an oil with viscozity SAE 15w40 and API Service SF/CC or lower;
- if not specified differently in the car manual, the maximum interval between two oil changes will be 15.000km but not more than 1 year.

### **PROPERTIES**

Viscosity Grade SAE	15W40
API Service	SF/CC
Density at 15°C [kg/m³]	850 - 890
Kinematic Viscosity at 100°C [mm²/s]	12.5-16.3
Viscosity Index, min	125
Flash Point [°C]min	210
Pour Point [°C] max	-30

### **PACKAGING**

□ 0.4Kg	☐ 1Kg	4Kg	☐ 15Kg	☐ 180Kg		
0.23L	0.45L	0.5L	0.6L	0.9L	$\boxtimes$ 1L	3L
∠ 4L					≥ 208L	