HEXOL INTERNATIONAL LTD



TECHNICAL DATA SHEET

HEXOL STANDARD 15W40

MOTOR OIL

PRODUCT DESCRIPTION

Hexol Standard 15W40 is a multigrade engine oil, produced from highly refined mineral base oils with additives providing adequate performance levels (detergent, dispersant, antioxidant, anti-wear, anticorrosive and antifoam agents, pour point depressant, and viscosity modifier). It is ideal for naturally aspirated and turbocharged engines of gasoline, diesel or LPG powered vehicles operating under severe conditions, where the manufacturer recomands this type of oil.

PERFORMANCE FEATURES

- exceeds API service CC/SC; MIL-L-46152 B;
- lubricates, cools and protects engines that operate at high temperatures;
- protects the engine from corrosion, wear, rust, deposits and varnish;
- reduces high temperature oxidation.

APPLICATION

- passenger cars and trucks equiped with gasoline, diesel or LPG engines where the producer recomands an oil with viscozity SAE 15w40 and API Service CC/SC or lower;
- if not specified differently in the car manual, the maximum interval between two oil changes will be 10.000km but not more than 1 year.

PROPERTIES

Viscosity Grade SAE	15W40
API Service	CC/SC
Density at 15°C [kg/m³]	860 - 890
Kinematic Viscosity at 100°C [mm²/s]	12.5-16.3
Viscosity Index, min	125
Flash Point [°C]min	215
Pour Point [°C] max	-25

PACKAGING

0.4Kg	□ 1Kg	4Kg	□ 15Kg	☐ 180Kg	
0.23L	0.45L	0.5L	0.6L	0.9L	
4L	□ 5L	□ 10L			