



HEXOL SUPERTRUCK 15W40

SUPER HIGH PERFORMANCE DIESEL (SHPD) MOTOR OIL

PRODUCT DESCRIPTION

Hexol Supertruck 15W40 is specially formulated for heavy duty diesel applications recommended for use in naturally aspirated or super-charged diesel truck engines, construction and farm equipments equipped with Euro III, Euro IV, or Euro V- without DPF. Hexol Supertruck 15W-40 is produced from highly refined mineral oils, with multi-purpose, well-balanced additive system (detergent/dispersant, anti-wear, antioxidant, anticorrosive, antifoam and acid neutralising agents and flow properties modifier).

PERFORMANCE FEATURES

- exceeds API Service CI-4/SL, ACEA E7-08, ACEA A3/B4-04 requirements;
- meets standards imposed by auto makers such Global DHD-1, Volvo VDS-3 TEDOM 258-3 Tatra TDS 40/16, MAN 3275-1, MB 228.3 229.1 235.28, VOLVO VDS-3, RENAULT VI RLD/RLD2, DAF, MACK EO-Mplus, JOHN DEERE 6020, 6120, 6220, 6320, 6420, 6420S, CATERPILLAR CAT ECF-1 ECF-2, AVIA DDC 93K215 Cummins CES 20077-20078, ZETOR;
- protects the engine from corrosion, wear, rust, deposits and varnish;
- reduces high temperature oxidation minimizing oil thickening;
- excellent high temperature stability;
- low valve train, ring and liner wear.

APPLICATION

- suitable for Euro III, Euro IV, and Euro V – without DPF- heavy duty diesel engines, equipping trucks, construction and farming equipments operating under severe conditions, where the manufacturer recommends an oil with API service CI-4/SL or lower performance;
- the drain interval will be according to the engine manufacturer indication.

PROPERTIES

Viscosity Grade SAE	15W40
API Service	CI-4/SL
Density at 15°C [kg/m ³]	860 – 900
Kinematic Viscosity at 100°C [mm ² /s]	12.5-16.3
Viscosity Index, min	135
Flash Point [°C]min	220
Pour Point [°C]max	-30

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L