



## HEXOL STANDARD T90 GL-5

GEAR OIL

### PRODUCT DESCRIPTION

HEXOL Standard T90 is a premium quality, monograde gear oils recommended to be used for differentials, manual transmissions and gear boxes for passenger cars, truck, farm machines, industrial and construction equipment. Is formulated from highly refined base oils with a well balanced additives package (anti-wear, anti-oxidant, anti-corrosive and anti-foam).

### PERFORMANCE FEATURES

- meets API Service GL-5 requirements as well as ST-OG 19/2005, JICASE MS, MASSEY FERGUSON M1110, Volvo 7325;
- lubricant for high load gears;
- good wear protection;
- minimizes rust and corrosion even in the presence of moisture;
- reduced foaming.

### APPLICATION

- can be used as an lubricant for transmissions, differentials, oil lubricated bearings, in passenger cars, trucks, buses, construction machines and industrial equipment;

### PROPERTIES

Viscosity Grade SAE	T90
API Service	GL-5
Density at 15°C [kg/m <sup>3</sup> ]	870 – 900
Kinematic Viscosity at 100°C [mm <sup>2</sup> /s]	13.5-24
Flash Point [°C ]min	210
Pour Point [°C ]max	-25

### PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input checked="" type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L