HEXOL INTERNATIONAL LTD



TECHNICAL DATA SHEET

HEXOL TURBODIESEL 15W40

MOTOR OIL

PRODUCT DESCRIPTION

HEXOL TURBODIESEL 15W40 is a multigrade diesel engine oil for heavy duty diesel engines operating under severe conditions. Recomanded for naturally aspirated and turbocharged diesel engines. Formulated with high rafinated mineral oil and additives (detergent-dispersants, antioxidants, anti-wear, corrosion- and foam inhibitors) and viscosity modifiers. Exceeds API CF/SF requirements.

PERFORMANCE FEATURES

- exceeds API Service CF/SF, ACEA E2-96, ACEA A3/B4-04 requirements;
- meets standards imposed by auto makers such VW 500.00, 501.1, MB 229.1, VOLVO VDS, MAN271, RENAULT RLD-2 RN0700 RN0710, FORD WS-M2, FIAT 9.55535-N2;
- protects the engine from corrosion, wear, rust, deposits and varnish;
- reduces high temperature oxidation minimizing oil thickening;
- excellent high temperature stability;
- low valve train, ring and liner wear.

APPLICATION

- recomanded for naturally aspirated and turbocharged diesel engines if the engine manufacturer specifies API service CF/SF or lower performance;
- the drain interval will be according to the engine manufacturer indication.

PROPERTIES

Viscosity Grade SAE	15W40
API Service	CF/SF
Density at 15°C [kg/m³]	860 - 890
Kinematic Viscosity at 100°C [mm²/s]	12.5-16.3
Viscosity Index, min	134
Flash Point [°C]min	230
Pour Point [°C]max	-27

PACKAGING

U.4Kg	□ TK8	∐ 4Kg	T2K8	TANKS		
0.23L	0.45L	0.5L	0.6L	0.9L	□ 1L	3L
	□ 5L	□ 10L				X 1000L