



HEXOL KA 22 – KA 32 – KA 46 – KA 68

COMPRESSOR OIL – CIRCULATION OIL – MACHINE TOOL OIL

PRODUCT DESCRIPTION

HEXOL KA are high quality ashless, zinc free, compressor oils specially formulated for use in lubricating any type of fixed and mobile compressor, where the manufacturer recommends an oil with these characteristics. Hexol KA are produced from highly refined mineral base oils with a well-balanced additive system such as: anti-corrosion, anti-wear, anti-oxidant, detergent and anti-foam additives.

PERFORMANCE FEATURES

- meets ISO-L-DAA, DAB, DAH, DAG; DIN 51506 – VBL, VCL, VDL; DIN 51524-2 (HLP);
- excellent wear protection;
- long-term oxidation stability;
- low foaming, rapid air and water separation;
- compatible with other conventional compressor oils;

APPLICATION

- are highly recommended for lubricating single- or multi-stage heavy duty, fixed or mobile compressors;
- also recommended for lubricating rotary screw compressors used in stationary and mobile applications;
- can be used as hydraulic fluid where a high quality oil is recommended.

PROPERTIES

Viscosity Grade ISO	22	32	46	68
Density at 15°C [kg/m ³]	880	890	895	895
Kinematic Viscosity at 40°C [mm ² /s]	19.8-24.2	28.8-35.2	41.4-50.6	61.2-74.8
Flash Point [°C]min	215	220	225	225
Pour Point [°C]max	-25	-25	-25	-25

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input checked="" type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L