



HEXOL STOU 10W30 – 10W40 – 15W40

SUPER TRACTOR OIL UNIVERSAL

PRODUCT DESCRIPTION

HEXOL STOU 10W30 – 10W40 – 15W40 are universal oils design for the latest generation of agricultural tractors, made from high quality mineral and synthetic base oils. Its rheological properties and combination of additives have been specially formulated to meet the quality requirements of the most modern tractors and agricultural machines. It offers extraordinary protection to the engine due to its anti-wear properties as well as its special cold flow properties.

PERFORMANCE FEATURES

- meets the requirements of API CG-4/SF, API GL-4, ACEA E3;
- meets the specifications of Massey Fergusson CMS 1145, 1144, 1139; Ford M2C159B; Allison C4; ZF TE ML 06A, 06B, 06C, 06D, 07B; Caterpillar TO-2; John Deere J27; MB 227.1, MB 228.1, MB 228.3; MAN 271; MIL-L-2104D; New Holland 82009201/2/3; Case New Holland MAT3525, 3526 and other types of vehicles or equipment whose manufacturers recommend that classification;
- excellent properties regarding the pour point;
- suitable as engine oil, transmission and hydraulic system;
- outstanding protection against wear and friction control;
- extraordinary cleaning of systems.

APPLICATION

- satisfies the most demanding requirements for engine, transmission -together with wet brakes- and tractor hydraulic systems, final transmissions (PTO) and power steering, in a wide range of operating temperatures;
- meets the demanding requirements of a STOU (Super Tractor Oil Universal) type lubricant;
- it is recommended to be used throughout the year.

PROPERTIES

Viscosity Grade SAE	10W30	10W40	15W40
Density at 15°C [kg/m ³]	880	885	895
Kinematic Viscosity at 100°C [mm ² /s]	9.3 – 12.5	12.5 – 16.3	12.5 – 16.3
Viscosity Index, min	140	140	140
Flash Point [°C] min	210	220	225
Pour Point [°C] max	-30	-30	-30

PACKAGING

<input type="checkbox"/> 0.4kg	<input type="checkbox"/> 1kg	<input type="checkbox"/> 4kg	<input type="checkbox"/> 15kg	<input type="checkbox"/> 180kg	<input type="checkbox"/> 1l	<input type="checkbox"/> 3l
<input type="checkbox"/> 0.23l	<input type="checkbox"/> 0.45l	<input type="checkbox"/> 0.5l	<input type="checkbox"/> 0.6l	<input type="checkbox"/> 0.9l	<input type="checkbox"/> 208l	<input type="checkbox"/> 1000l
<input type="checkbox"/> 4l	<input type="checkbox"/> 5l	<input checked="" type="checkbox"/> 10l	<input checked="" type="checkbox"/> 20l	<input checked="" type="checkbox"/> 60l	<input checked="" type="checkbox"/> 208l	<input checked="" type="checkbox"/> 1000l

HEXOL®

HEXOL LUBE SRL

Zona Metropolitană Oradea • 417166 Paleu, Str. Ardealului nr. 1A, jud. Bihor • România
Telefon +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com