



HEXOL SYNLINER TORSION 75W90

GEAR OIL

PRODUCT DESCRIPTION

HEXOL Synliner Torsion 75W90 is a synthetic blend transmission oil with very high performance, having excellent lubricating characteristics, ensuring maximum oil change intervals. It is produced from high quality base oils using a complex additive package, ensuring excellent anti-wear and extreme pressure (EP) protection, extended oil change intervals.

PERFORMANCE FEATURES

- suitable to use for the following specifications API Service GL-5 and GL-4; SAE J2360, MT-1, Volvo 97312, MAN 342 Typ S1, S2, M1, M2, M3, Arvin Meritor 076-N, Meritor (EU) Extended Drain, ZF TE- ML -02B, 05B, 12L, 12N, 16F, 17B, 19C, 21A, 21B, Scania STO 2:0 A, Scania STO 2:0 G FS, DAF, Mack GO-J Plus, Iveco 18-1805 Extended Drain Requirements, VW G 052 – 145 A2, 178, 726, 911, Ford WSD-M2-C200-C, MB 235.8, IVECO 18-1805;
- excellent thermal and antioxidant stability of the oil;
- excellent fluidity and performance even at low temperatures.

APPLICATION

- recommended for use in gearboxes, steering systems, differentials that equip cars, vans, construction and agricultural equipment where the manufacturer recommends an oil with the parameters mentioned below;
- can also be used as a lubricant in hypoid gears, in industrial equipment;
- it has an extremely long drain interval, depending on the recommendations of the equipment manufacturer.

PROPERTIES

Viscosity Grade	SAE 75W90
API Service	GL-5
Density at 15°C [kg/m ³]	885
Kinematic Viscosity at 100°C [mm ² /s]	13.5 - 24
Viscosity Index	160
Flash Point [°C]	190
Pour Point [°C]	-41
Dinamic Viscosity at -40°C (Brookfield), [cP], max	150000

PACKAGING

<input type="checkbox"/> 0.4kg	<input type="checkbox"/> 1kg	<input type="checkbox"/> 4kg	<input type="checkbox"/> 15kg	<input type="checkbox"/> 180kg		
<input type="checkbox"/> 0.23l	<input type="checkbox"/> 0.45l	<input type="checkbox"/> 0.5l	<input type="checkbox"/> 0.6l	<input type="checkbox"/> 0.9l	<input checked="" type="checkbox"/> 1l	<input type="checkbox"/> 3l
<input type="checkbox"/> 4l	<input checked="" type="checkbox"/> 5l	<input checked="" type="checkbox"/> 10l	<input checked="" type="checkbox"/> 20l	<input checked="" type="checkbox"/> 60l	<input checked="" type="checkbox"/> 208l	<input checked="" type="checkbox"/> 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.

HEXOL®