



HEXOL SYNLINER ULTRATRUCK 15W40

MOTOR OIL

PRODUCT DESCRIPTION

Hexol SYNLINER UltraTruck 15W40 is an extra high performance, low ash, synthetic engine oil, developed for commercial diesel vehicles fitted with the latest exhaust gas treatment equipment.

PERFORMANCE FEATURES

- meets the requirements of ACEA E9, ACEA E7, ACEA E6, API CK-4/SN and API CK-4/SM;
- complies with the standards imposed by car manufacturers, such as: MB 228.51, 228.31; MAN 3477, 3575, 3677, 3271-1; DETROIT DIESEL DFS 93K222, DFS 93K218; Volvo VDS-4.5, VDS-4, VDS-3; Renault RLD-4, RLD-3; IVECO TLS E9; CAT ECF-1a/ECF-2/ECF-3; MACK EOS 4.5, EO-OPP; Deutz DQC IV-10LA; MTU Type 3.1, 2.1; JASO DH-2, DHD-1; Cummins CES20081/CES20086; Scania LA-2, LA, LDF; DAF Extended Drain, CNG, Ford WSS-M2C171-F1;
- extremely long oil change interval, offers excellent reliability at start-up even at extremely low temperatures;
- low ash content, prolongs the life of the exhaust gas treatment devices.

APPLICATION

- recommended for engines that equip commercial vehicles operating at both high and low speeds, equipped with modern gas treatment systems (EGR exhaust recirculation, DOC catalytic oxidation, DPF particle filter) corresponding to Euro IV pollution standards, Euro V, Euro VI, where the manufacturer recommends a lubricant with the following characteristics;
- also recommended for engines without noise reduction systems or for locomotives, construction, mining and agricultural equipment;
- the oil change interval is approx. 100.000 Km depending on the manufacturer's recommendation.

PROPERTIES

Viscosity grade SAE	15W40
Density at 15°C [kg/m ³], max	890
Kinematic Viscosity at 100°C [mm ² /s]	12.5 – 16.3
Viscosity Index, min	155
HTHS Viscosity at 150°C [cP]	4.1
Flash Point [°C], min	229
Pour Point [°C], max	-36

PACKAGING

<input type="checkbox"/> 0.4kg	<input type="checkbox"/> 1kg	<input type="checkbox"/> 4kg	<input type="checkbox"/> 15kg	<input type="checkbox"/> 180kg		
<input type="checkbox"/> 0.23l	<input type="checkbox"/> 0.45l	<input type="checkbox"/> 0.5l	<input type="checkbox"/> 0.6l	<input type="checkbox"/> 0.9l	<input type="checkbox"/> 1l	<input type="checkbox"/> 3l
<input type="checkbox"/> 4l	<input checked="" type="checkbox"/> 5l	<input checked="" type="checkbox"/> 10l	<input checked="" type="checkbox"/> 20l	<input checked="" type="checkbox"/> 60l	<input checked="" type="checkbox"/> 208l	<input checked="" type="checkbox"/> 1000l

HEXOL®