



HEXOL SYNLINER ULTRATRUCK 10W40

ULTRA HIGH PERFORMANCE DIESEL (UHPD) MOTOR OIL

PRODUCT DESCRIPTION

Hexol Synliner UltraTruck 10W40 is an extra high performance, low ash, synthetic engine oil, developed for commercial diesel vehicles fitted with the latest exhaust gas treatment equipment. It meets the requirements of a wide range of performance levels of the most outstanding engine manufacturers such as: Mercedes-Benz, MAN, Volvo, Renault, Deutz, Caterpillar, Cummins, Mack, Detroit Diesel and others, together with the most stringent US and European specifications for diesel engine oils. This product is suitable for heavy-duty road and off-road vehicles.

PERFORMANCE FEATURES

- Exceeds API Service CJ-4/SM, CI-4 and SN, ACEA E9-12 and E7-12 requirements
- It meets standard requirements imposed by automakers such as: MAN M 3575, Volvo VDS-4 and VDS-3, Renault RLD-3 and RLD-2, Caterpillar ECF- 1a, ECF- 2 and ECF- 3, MACK EO-O Premium plus, Deutz DQC III-10LA, MTU Type 2.1, DDC 93K218, and Cummins CES20081
- Provides reliable start-up and operation even at extremely low temperatures
- Long oil drain interval
- Low ash content, guarantees long lifetime of exhaust gas treatment devices
- This oil maintains its properties for up to 5 years when in its original container, sealed, and stored away from any heat source and direct sunlight (storage temperature max. 40°C)

APPLICATION

- Suitable for commercial vehicles operating at low or high speeds, equipped with Exhaust Gas Recirculation (EGR), Diesel Oxidation Catalyst (DOC) or Diesel Particulate Filter (DPF), complying with Euro IV, Euro V and Euro VI emission requirements, where the manufacturer recommends oil with the above listed properties
- Compatible with diesel engines in railway, mining, construction, and agricultural machines
- The drain interval is up to 100.000 km, depending on the engine manufacturer's recommendation

PROPERTIES

Viscosity Grade SAE	10W40
Density at 15°C [kg/m ³]	850 - 880
Kinematic Viscosity at 100°C [mm ² /s]	12.5-16.3
Viscosity Index, min	150
Flash Point [°C]min	220
Pour Point [°C]max	-36
Base number (BN)[mg KOH/g]	8.5

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg		
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 4L	<input checked="" type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L	<input checked="" type="checkbox"/> 208L	<input checked="" type="checkbox"/> 1000L

HEXOL LUBE SRL

Oradea Metropolitan Area • 417166 Paleu, 1A Ardealului st, Bihor • Romania
Tel +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com

REV.
2019