



HEXOL UTTO 80W

UNIVERSAL TRACTOR OIL

PRODUCT DESCRIPTION

HEXOL UTTO 80W is an universal tractor oil, with special rheological properties recommended to use all year round in differentials, gear boxes, stirring systems, hydraulic systems or any other type of equipment where the manufacturer recommends this type of oil.

PERFORMANCE FEATURES

- meets API Service GL-4 requirements;
- reacts with metal surfaces to prevent gear pitting and reduce wear;
- reduces corrosion and rust;
- contains anti-oxidative and anti-foaming additives.

APPLICATION

- for farm, industrial or construction equipments as well as any other equipments requiring API Service GL-4 specifications;
- recommended for all year round use.

PROPERTIES

Viscosity Grade SAE	80W
Density at 15°C [kg/m ³]	850 – 880
Kinematic Viscosity at 40°C [mm ² /s]	52-80
Kinematic Viscosity at 100°C [mm ² /s]	7-11
Viscosity Index, min	90
Flash Point [°C]min	220
Pour Point [°C]max	-25

PACKAGING

<input type="checkbox"/> 0.4Kg	<input type="checkbox"/> 1Kg	<input type="checkbox"/> 4Kg	<input type="checkbox"/> 15Kg	<input type="checkbox"/> 180Kg	<input type="checkbox"/> 1L	<input type="checkbox"/> 3L
<input type="checkbox"/> 0.23L	<input type="checkbox"/> 0.45L	<input type="checkbox"/> 0.5L	<input type="checkbox"/> 0.6L	<input type="checkbox"/> 0.9L	<input type="checkbox"/> 208L	<input type="checkbox"/> 1000L
<input type="checkbox"/> 4L	<input type="checkbox"/> 5L	<input checked="" type="checkbox"/> 10L	<input checked="" type="checkbox"/> 20L	<input checked="" type="checkbox"/> 60L		

HEXOL INTERNATIONAL LTD

HEXOL LUBE SRL

Oradea Metropolitan Area • 417166 Paleu, 1A Ardealului st, Bihor • Romania
Tel +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com

REV.
2019