



## HEXOL LI CA2 PREMIUM GREASE

### PRODUCT DESCRIPTION

HEXOL LI CA2 Premium is a grease manufactured by condensation of mineral base oils with lithium/calcium soap, offering the benefits of both saponification agents, ensuring excellent water and friction resistance and a good protection against corrosion and wear in various applications, in working conditions especially at temperatures between -30°C and +110°C.

### PERFORMANCE FEATURES

- meets ISO 6743-9: L-XCCEA 2; DIN 51502: K2H-30; NLGI-2 requirement;
- specially formulated to ensure a good resistance to water washing;
- has a great affinity with metals ensuring good protection of bearing surfaces against wear and corrosion even when grease is contaminated with water;
- free of toxic components.

### APPLICATION

- specially recommended for slide bearings and bearings, operated at moderate speed and in a high humidity environment;
- industrial equipment and agricultural machinery equipped with greasing points, where the manufacturer recommends the use of a grease from this category.

### PROPERTIES

Appearance	brown, homogenous
Dropping Point [°C]	170
Penetration after 60 strokes at 25°C [0,1 mm]	260-300
Water content	none
Free alkali (Na OH)[%], max	0.15
Colloidal stability g oil/100g grease, max.	15

### PACKAGING

<input type="checkbox"/> 0.4kg	<input type="checkbox"/> 1kg	<input checked="" type="checkbox"/> 4kg	<input checked="" type="checkbox"/> 15kg	<input checked="" type="checkbox"/> 180kg		
<input type="checkbox"/> 0.23l	<input type="checkbox"/> 0.45l	<input type="checkbox"/> 0.5l	<input type="checkbox"/> 0.6l	<input type="checkbox"/> 0.9l	<input type="checkbox"/> 1l	<input type="checkbox"/> 3l
<input type="checkbox"/> 4l	<input type="checkbox"/> 5l	<input type="checkbox"/> 10l	<input type="checkbox"/> 20l	<input type="checkbox"/> 60l	<input type="checkbox"/> 208l	<input type="checkbox"/> 1000l