

# TEHNICAL DATA SHEET

## **HEXOL HYDROMOTOR SAE 10W**

HYDRAULIC - MOTOR OIL

#### PRODUCT DESCRIPTION

HEXOL HYDROMOTOR SAE 10W is a high-quality monograde oil, recommended for use in engines and hydraulic systems, which equip construction, mining, material handling machinery or other types of machinery where the manufacturer recommends the use of such a lubricant.

Formulated from mineral base oils with a complex additive package, it ensures excellent performance in operation for engine and hydraulic system.

#### PERFORMANCE FEATURES

- meets the API CF requirements, as well as the requirements of the DIN 51524 part2 (HLP) specifications.
- excellent anti-wear protection, ensures safe operation of the parts in contact;
- excellent anti-corrosion protection, long-lasting protection of components;
- excellent oxidative and thermal stability, the formation of acids and sediments is reduced;
- low foaming tendency;
- good fluidity at low temperatures.

#### APPLICATION

- engines of machines where the manufacturer recommends the use of a monograde lubricant, with SAE 10W viscosity and API CF specification;
- the hydraulic system of construction, mining, material handling machinery or other types of machinery where the manufacturer recommends the use of such a lubricant

### **PROPERTIES**

Viscosity Grade	SAE 10W
API Service	CF
Density at 15°C [kg/m³]	880
Kinematic Viscosity at 100°C [mm²/s] min.	4.1
Viscosity Index, min	95
Flash Point [°C ]min	200
Pour Point [°C ]max	-30

#### **PACKAGING**

0.4kg	1kg	4kg	15kg	180kg		
0.231	0.45l	0.5l	0.6l	0.91	<u> </u>	<u> </u>
41	□ 5I	X 10l		<b>⊠</b> 60I	× 2081	X 1000I

