

TEHNICAL DATA SHEET

HEXOL UTTO 80W – 10W30 PREMIUM

UNIVERSAL TRACTOR OIL

PRODUCT DESCRIPTION

HEXOL UTTO 80W – 10W30 Premium is a oil for hydraulic transmissions with special rheological properties, recommended for use throughout the year in tractors or other off-road vehicles on differentials, gearboxes, steering systems, hydraulic installations or other equipment to which the manufacturer recommends lubricating with such an oil. It is recommended for use in machines equipped with wet brakes. It consistes of high quality mineral oils and high-performance additives.

PERFORMANCE FEATURES

- meets the requirements of API GL-4;
- meets the specifications of the main agricultural machinery manufacturers: Massey-Ferguson 1145, Ford and International Harvester, John Deere J20D; J.I. Case; Case New Holland MAT 3525, 3526, 3505, 3540; Volvo VCE 1273.03; Eaton Vickers; White Farm Equipment, Allis Chalmers, Steiger, Caterpillar CAT TO-2; ZF TE-ML-03F, 05F, 06K, 17E, 21F; Allison C-4; Kubota Super UDT2; Parker (Denison) HF-2 or other types of vehicles or machinery whose manufacturers recommend the use of an oil with this classification;
- reacts with metal surfaces to prevent welding and to reduce wear;
- reduces corrosion and rust;
- contains anti-oxidative and anti-foaming additives.

APPLICATION

- for farm, industrial or construction equipments as well as any other equipments requiring a oil with the SAE 80W 10W30 viscosity and API Service GL-4 specifications;
- recommended for all year round use.

PROPERTIES

Viscosity Grade	SAE 80W – 10W30
API Service	GL-4
Density at 15°C [kg/m³]	900
Kinematic Viscosity at 100°C [mm²/s]	9.3 - 12.5
Viscosity Index, min	130
Flash Point [°C]min	210
Pour Point [°C]max	-25
DACKACING	

PACKAGING

0.4kg	1kg	4kg		180kg		
0.231	0.45l	0.5I	0.6I	0.91	1l	3I
41	□ 51	X 10I	× 20I	⋈ 601	× 2081	X 1000

HEXOL