



## HEXOL SYNLINER ULTRATRUCK MAXX 5W30 / 10W30 / 10W40 / 15W40

MOTOR OIL

### PRODUCT DESCRIPTION

HEXOL Synliner Ultratruck Maxx is a synthetic engine oil that ensures high performance and fuel economy in "heavy duty" (HD) operating conditions. Produced from synthetic base oils and a complex additive system with low levels of sulfur ash, phosphorus and sulfur (low SAPS), it provides excellent flow and lubrication characteristics. This oil meets the requirements of the most important associations of motor vehicle and machinery manufacturers.

### PERFORMANCE FEATURES

- meets the requirements of ACEA E7, ACEA E8, ACEA E11, API CK-4;
- complies with the requirements of the standards imposed by car manufacturers, such as: MB 228.51 / 228.31, MAN 3477 / 3575 / 3677 / 3271-1, DETROIT DIESEL DFS 93K222, DFS 93K218, DDC 93K219, Volvo VDS-4.5 / 4 / 3, Renault RLD-4 / RLD-3, JASO DH-2, IVECO TLS E9, CAT ECF-3, MACK EOS 4.5 / EO-OPP, Deutz DQC IV-10LA, MTU Type 3.1 / 2.1, DHD-1, Cummins CES20081 / CES20086, Scania LA-2 / LA / LDF, DAF Extended Drain, CHG, Ford WSS-M2C171-F1 and others.

### APPLICATION

- suitable for trucks and heavy tonnage machines, equipped with naturally aspirated diesel engines or turbo, equipped with particulate filters (DPF), exhaust gas recirculation systems (EGR) and selective catalytic reduction (SCR);
- the oil change interval is indicated by the engine manufacturer.

### PROPERTIES

Viscosity grade SAE	5W30	10W30	10W40	15W40
Density at 15°C [kg/m <sup>3</sup> ], max	870	875	880	890
Kinematic Viscosity at 100°C [mm <sup>2</sup> /s]	9.3-12.5	9.3-12.5	12.5-16.3	12.5-16.3
Viscosity Index	160	155	150	145
Flash Point [°C]	230	230	225	220
Pour Point [°C]	-45	-40	-38	-35

### PACKAGING

<input type="checkbox"/> 0.4kg	<input type="checkbox"/> 1kg	<input type="checkbox"/> 4kg	<input type="checkbox"/> 15kg	<input type="checkbox"/> 180kg		
<input type="checkbox"/> 0.23l	<input type="checkbox"/> 0.45l	<input type="checkbox"/> 0.5l	<input type="checkbox"/> 0.6l	<input type="checkbox"/> 0.9l	<input type="checkbox"/> 1l	<input type="checkbox"/> 3l
<input type="checkbox"/> 4l	<input checked="" type="checkbox"/> 5l	<input checked="" type="checkbox"/> 10l	<input checked="" type="checkbox"/> 20l	<input checked="" type="checkbox"/> 60l	<input checked="" type="checkbox"/> 208l	<input checked="" type="checkbox"/> 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.