

HEXOL SYNLINE SPRINT 5W30 – 5W40

MOTOR OIL

PRODUCT DESCRIPTION

HEXOL Synline Sprint is a high-quality, multigrade, synthetic blend oil, formulated from synthetic and mineral base oils and a package of additives with anti-corrosion, antioxidant, anti-wear, anti-foaming properties, recommended for year-round use in naturally aspirated or turbocharged gasoline, gas or diesel engines. The oil is compatible with E85 regulations regarding fuels with an ethanol content of 85%.

PERFORMANCE FEATURES

- suitable to use for the following specifications API Service SN/CF, ACEA A3/B4, ILSAC GF-5, VW 500.00, 501.01, 505.00, MB 229.1, Renault 0700, FORD WS-M2, PSA B71 2294, B71 2300, FIAT 9.55535-H2 and other types of vehicles whose manufacturers recommend an oil with this classification;
- protects the engine by controlling and minimizing varnish, resin, rust deposits;
- contains anti-wear, anti-corrosion and anti-foaming additives that extend the life of the engine ensuring its optimal operation;
- high viscosity index that allows for optimal thermal stability.

APPLICATION

- can be used in cars and vans with gasoline, gas or diesel engines where the manufacturer recommends using an oil with the performances mentioned above;
- the change interval is that indicated by the engine manufacturer.

PROPERTIES

Viscosity grade SAE	5W30	5W40
Density at 15°C [kg/m³], max	880	880
Kinematic Viscosity at 100°C [mm ² /s]	9.3-12.5	12.5-16.3
Viscosity Index	160	165
Flash Point [°C]	210	210
Pour Point [°C]	-40	-38

PACKAGING

0.4kg	1kg	4kg	15kg	180kg		
0.23	0.45	0.51	0.61	0.91	<u> </u>	31
4	51	🔀 10l	🔀 20l	🖂 60I	🔀 208l	🔀 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.