



HEXOL CA2 PREMIUM GREASE

PRODUCT DESCRIPTION

HEXOL CA2 Premium is a general purpose anhydrous calcium soap based grease with excellent adhesion to metals and very good water resistance. Recommended for the lubrication of bearings and raceways found in the automotive, metallurgical and construction industries, agricultural machinery, where very good sealing against dust and water is required. It ensures high-performance lubrication in working conditions between -20 °C and +100 °C. Formulated from special mineral oil and anhydrous calcium soap, the product does not change its consistency even under long-term storage conditions.

PERFORMANCE FEATURES

- can be used for specifications: ISO 6743-9: L-XBBHA 2; DIN 51502: K2G-20; NLGI 2;
- excellent adhesion to metals;
- water resistant;
- has a fine structure;
- long-lasting protection against corrosion;
- does not contain toxic components.

APPLICATION

- especially recommended for industrial mechanisms (pivoting movements, joints, bearings) and agricultural machinery.

PROPERTIES

Appearance	Red, homogeneous
Dropping point [°C], min	140
Penetration after 60 strokes at 25°C(0.1mm)	265-295
Corrosion at 100 °C / 24 h (steel)	Pass

PACKAGING

☒ 0.4kg	☒ 1kg	☒ 4kg	☒ 15kg	☒ 180kg	☐ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 208l	☐ 1000l
☐ 4l	☐ 5l	☐ 10l	☐ 20l	☐ 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.