



HEXOL LA 22 – LA 32 – LA 46

SLIDING BEARING OIL

PRODUCT DESCRIPTION

HEXOL LA 22 – LA 32 – LA 46 are oils intended for bearing lubrication, obtained from refined mineral oils, characterized by high flammability temperatures, low volatility, low flow temperatures so as to provide operational safety and high rheological properties.

PERFORMANCE FEATURES

- can be used for specifications DIN 51501 L-AN, ISO 6743-2 ISO-L-FC, DIN 51524-1(HL), DIN 51517-2 (CL);
- contain antioxidant, anticorrosive and antifoaming additives;
- remain stable even under conditions of exposure to moisture and extreme temperatures.

APPLICATION

- for the lubrication and protection of machine tools, bearings in mixer reducers in the pulp and paper industry, steel industry, machine construction, speed variators as well as in other fields.

PROPERTIES

Viscosity gradea ISO	22	32	46
Density at 15°C [kg/m ³], max	880	890	895
Kinematic Viscosity at 40°C [mm ² /s]	19.8-24.2	28.8-35.2	41.4-50.6
Flash Point [°C]	215	220	225
Pour Point [°C]	-25	-25	-25

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg		
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 1l	☐ 3l
☐ 4l	☐ 5l	☒ 10l	☒ 20l	☒ 60l	☒ 208l	☒ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.