



HEXOL LI CA2 PREMIUM GREASE

PRODUCT DESCRIPTION

HEXOL LI CA2 Premium is a grease manufactured by condensing mineral base oils with lithium and calcium soap, offering benefits from both saponification agents, ensuring excellent water and friction resistance and good protection against corrosion and wear in various applications, in working conditions located especially in the temperature range of -30 °C and +130 °C.

PERFORMANCE FEATURES

- can be used for specifications: ISO 6743-9: L-XCCEB 2; DIN 51502: KP2K-30; NLGI-2;
- specially formulated to ensure very good resistance to water washout;
- has a high affinity with metals ensuring good protection of bearing surfaces against wear and corrosion even when the grease is contaminated with water;
- does not contain toxic components.

APPLICATION

- especially recommended for sliding bearings and roller bearings, operated at moderate speeds, in environments with high humidity;
- industrial equipment and agricultural machinery equipped with greasing points, where the manufacturer recommends the use of a grease from this category.

PROPERTIES

Appearance	Red, homogeneous
Dropping point [°C], min	170
Penetration after 60 Strokes at 25°C(0.1mm)	260-300
Corrosion at 100 °C / 24 h (copper)	passed

PACKAGING

☐ 0.4kg	☐ 1kg	☒ 4kg	☒ 15kg	☒ 180kg		
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 1l	☐ 3l
☐ 4l	☐ 5l	☐ 10l	☐ 20l	☐ 60l	☐ 208l	☐ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.