



HEXOL MF 15 – MF 22

FINE MECHANICAL OIL

PRODUCT DESCRIPTION

Hexol MF 15 – MF 22 are oils intended for the lubrication and care of fine mechanical elements of various machines and equipment, such as those in the textile and leather industry or various fine mechanical instruments.

PERFORMANCE FEATURES

- can be used for ISO 6743-10 specification;
- contain additives that prevent corrosion and oxidation;
- remain stable even under conditions of exposure to moisture and extreme temperatures;
- do not contain silicone and acids.

APPLICATION

- recommended for use in precision engineering technologies, measuring instruments, sewing machines, knitting machines, fishing gear.

PROPERTIES

Viscosity gradea ISO	15	22
Density at 15°C [kg/m ³], max	850	860
Kinematic Viscosity at 40°C [mm ² /s]	13 - 17	19 - 24
Flash Point [°C]	180	180
Pour Point [°C]	-8	-12

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg		
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 1l	☐ 3l
☐ 4l	☐ 5l	☒ 10l	☒ 20l	☒ 60l	☒ 208l	☒ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.