



HEXOL SPRINT 2T API TC MOTOR OIL

PRODUCT DESCRIPTION

HEXOL Sprint 2T API TC is a specially formulated oil for high-performance two-stroke engines, containing mineral base oils, antioxidant, anti-corrosion, anti-wear additives, dispersants and depressants, resulting in a reduced amount of ash. Usable all year round in two-stroke engines with mixed or injection lubrication, air or water cooled.

PERFORMANCE FEATURES

- can be used for specifications: API TC; JASO FD; ISO-L-EGD and some manufacturers such as Aprilia, Honda, Suzuki, Vespa, Piaggio, Yamaha, Husqvarna, KTM;
- ensures proper lubrication and protection, avoiding spark plug fouling, exhaust window coating and piston ring wear, keeping the piston clean and reducing deposits in the combustion chamber;
- used in the recommended proportions, reduces exhaust emissions.

APPLICATION

- intended for two-stroke engines that equip motorcycles, mopeds, scooters, motorboats, ATVs, snowmobiles, gardening equipment, for which the manufacturer recommends the use of an oil for mixing with these characteristics;
- when determining the oil/petrol ratio, the recommendations of the engine manufacturer must be taken into account.

PROPERTIES

Density at 15°C [kg/m ³], max	885
Kinematic Viscosity at 40°C [mm ² /s]	41.4 – 50.6
Kinematic Viscosity at 100°C [mm ² /s]	6.3 – 7
Flash Point [°C]	180
Pour Point [°C]	-20
Color	red

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg	☒ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☒ 208l	☒ 1000l
☐ 4l	☒ 5l	☒ 10l	☒ 20l	☒ 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.