



HEXOL STANDARD 20W50

MOTOR OIL

PRODUCT DESCRIPTION

HEXOL Standard SAE 20W50 is a high-quality multigrade oil, formulated from mineral base oils with a high-performance additive package, recommended for use in all seasons, in gasoline or gas engines, naturally aspirated diesel or older generation turbo.

PERFORMANCE FEATURES

- can be used for specifications: API SF/CC;
- contains anti-wear, anti-corrosion and anti-foam additives, which extend engine life, ensuring optimal operation;
- provides lubrication, cooling and protection of engines operating at high temperatures;
- controls and minimizes deposits and sediments of varnish, rust, carbon, etc.

APPLICATION

- cars and vans, machinery, aggregates with gasoline or gas, diesel engines for which the manufacturer recommends the use of a lubricant with the performances mentioned above;
- the optimal solution for mixed car fleets;
- the replacement interval is that indicated by the engine manufacturer.

PROPERTIES

Viscosity Grade SAE	20W50
API Service	SF/CC
Density at 15°C [kg/m ³], max	895
Kinematic Viscosity at 100°C [mm ² /s]	16.3 – 21.9
Viscosity Index	110
Flash Point [°C]	220
Pour Point [°C]	-21

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg		
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 1l	☐ 3l
☐ 4l	☐ 5l	☒ 10l	☒ 20l	☒ 60l	☒ 208l	☒ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.