



HEXOL 2T STANDARD – ECO 2T

MIX OIL

PRODUCT DESCRIPTION

HEXOL 2T Standard / ECO 2T are oils specially formulated for two-stroke engines, containing mineral base oils, antioxidant, anti-corrosion, anti-wear, dispersant and depressant additives, with a low ash content.

Usable all year round in engines with mixed or injection lubrication, air-cooled.

PERFORMANCE FEATURES

- can be used for API TA specifications;
- provides proper lubrication and protection, avoiding spark plug fouling, exhaust port coating and piston ring wear, keeping the piston clean and reducing combustion chamber deposits;
- used in the recommended proportions, reduces smoke emissions.

APPLICATION

- intended for two-stroke engines of gardening equipment, mopeds, scooters, cars, motorboats, whose manufacturers recommend the use of such oil;
- when determining the oil/petrol ratio, the manufacturer's recommendations must be taken into account;
- a mixture richer in oil than recommended can cause premature wear of the engine and increase pollutant emissions.

PROPERTIES

	2T Standard	2T Eco
Density at 15°C [kg/m ³], max	900	900
Kinematic Viscosity at 40°C [mm ² /s]	41.4 – 50.6	41.4 – 50.6
Kinematic Viscosity at 100°C [mm ² /s]	6.3 – 7	6.3 – 7
Flash Point [°C]	180	180
Pour Point [°C]	-12	-12
Color	red	green

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg		
☐ 0.23l	☐ 0.45l	☒ 0.5l	☐ 0.6l	☐ 0.9l	☒ 1l	☐ 3l
☐ 4l	☒ 5l	☒ 10l	☒ 20l	☒ 60l	☒ 208l	☒ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.