



HEXOL STANDARD GARDEN 10W30

MOTOR OIL

PRODUCT DESCRIPTION

HEXOL Standard Garden 10W30 is a high-quality multigrade oil, produced from highly refined mineral base oils, using an additive package, recommended for use in all seasons, in gasoline engines, subject to intensive exploitation.

Recommended for use in agricultural machinery and gardening equipment, reducing oxidation and oil thinning generated by sustained operation at high temperatures, ensuring good stability.

PERFORMANCE FEATURES

- can be used for API SF/CF specifications as well as for some manufacturers of garden machinery such as MTD, Briggs & Stratton, Honda, Tecumseh, Stihl, Hecht, Husqvarna and others;
- contains anti-wear, anti-corrosion and anti-foam additives that extend engine life ensuring optimal operation;
- provides lubrication, cooling and protection of engines operating at high temperatures;
- controls and minimizes deposits and sediments of varnish, rust, carbon, etc.

APPLICATION

- for agricultural machinery and gardening equipment with petrol engines, for which the manufacturer recommends the use of a lubricant with the performances mentioned above;
- the replacement interval is that indicated by the engine manufacturer.

PROPERTIES

Viscosity grade SAE	10W30
API Service	SF/CF
Density at 15°C [kg/m ³], max	890
Kinematic Viscosity at 100°C [mm ² /s]	9.3 – 12.5
Viscosity Index	125
Flash Point [°C]	210
Pour Point [°C]	-30

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg		
☐ 0.23l	☐ 0.45l	☐ 0.5l	☒ 0.6l	☐ 0.9l	☐ 1l	☐ 3l
☐ 4l	☒ 5l	☒ 10l	☒ 20l	☒ 60l	☒ 208l	☒ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.

HEXOL®