



HEXOL SUPERDIESEL 15W40

MOTOR OIL

PRODUCT DESCRIPTION

Hexol SuperDiesel 15W40 is a high-quality, multigrade mineral engine oil, recommended for all-season use in diesel, gasoline or gas engines that meet EURO III, IV and are not equipped with DPF. Formulated with high-quality base oils and high-performance additives, it meets the lubrication requirements of heavy-duty diesel engines.

PERFORMANCE FEATURES

- can be used for API CI-4/SL, ACEA E7, ACEA A3/B4, VW 500.00 / 501.01 / 505.00, VOLVO VDS-3, MAN 3275-1, MB 228.3, MTU 2.0, PSA B71 2295, RENAULT 0710, CAT ECF-1/2, Cummins CES 20077 / 20078, MACK EO- N, Detroit Diesel DDC 93K215, Global DHD-1, DEUTZ DQC III, FIAT 9.55535-H2;
- contains anti-wear, anti-corrosion, anti-foaming additives, which extend engine life ensuring optimal operation;
- provides lubrication, cooling and protection of engines operating at high temperatures;
- controls and minimizes deposits and sediments of varnish, rust, carbon, etc.;
- reduces oxidation and oil thinning caused by sustained operation at high temperatures, ensuring good stability.

APPLICATION

- diesel engines that equip cars, vans, construction equipment, agricultural equipment, subjected to intensive exploitation, if the manufacturer recommends an oil with the performances mentioned above;
- the replacement interval is that indicated by the engine manufacturer.

PROPERTIES

Viscosity grade SAE	15W40
Density at 15°C [kg/m ³], max	885
Kinematic Viscosity at 100°C [mm ² /s]	12.5 – 16.3
Dinamic Viscosity at -20°C [cP], max	7000
Viscosity Index	135
Flash Point [°C]	220
Pour Point [°C]	-30

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg	☒ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☒ 208l	☒ 1000l
☒ 4l	☒ 5l	☒ 10l	☒ 20l	☒ 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.

HEXOL®