



HEXOL SYNLIN 4T MOTOSPRINT 10W40

MOTOR OIL

PRODUCT DESCRIPTION

HEXOL Synline 4T Moto Sprint 10W40 is a high-quality, multigrade, synthetic blend oil, formulated from synthetic and mineral base oils and a package of additives with anti-corrosion, antioxidant, anti-wear, anti-foaming properties, being recommended for use throughout the year in gasoline engines, naturally aspirated or turbocharged, that equip motorcycles, mopeds, and motorboats equipped with four-stroke engines.

PERFORMANCE FEATURES

- can be used for API Service SL, ACEA A3/B4, IASO MA-2, Aprilia, BMW, Ducatti, Honda, Kawasaki, Suzuki, Yamaha, Piaggio, Peugeot and other types of motorcycles, mopeds, motorboats and cars, whose manufacturers recommend an oil with this classification;
- protects the engine by controlling and minimizing varnish, resin, rust deposits;
- contains anti-wear, anti-corrosion and anti-foam additives that extend the life of the engine ensuring its optimal operation;
- reduces oxidation by maintaining its properties for a long time, even used at high speeds and forces.

APPLICATION

- motorcycles, mopeds and boats with 4-stroke engines, water- or air-cooled where the manufacturer recommends the use of an oil with the above specifications.

PROPERTIES

Viscosity grade SAE	10W40
API Service	SL
Density at 15°C [kg/m ³], max	880
Kinematic Viscosity at 100°C [mm ² /s]	12.5 – 16.3
Dinamic Viscosity at -25°C [cP], max	7000
Viscosity Index	150
Flash Point [°C]	210
Pour Point [°C]	-33

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg	☒ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 208l	☐ 1000l
☐ 4l	☐ 5l	☐ 10l	☐ 20l	☐ 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.