



HEXOL SYNLINE FUSION

MOTOR OIL (PCMO)

PRODUCT DESCRIPTION

HEXOL Synline Fusion is a fully synthetic, mid-SAPS engine oil for passenger cars equipped with Diesel, gasoline and hybrid engines. Formulated to provide superior protection against the challenges associated with the lubrication of small engines and to be compatible with exhaust after-treatment systems, including DPFs, GPFs, EGRs. Low speed pre-ignition (LSPI) is mitigated against to protect modern down sized gasoline powered engines. Incorporates premium deposit control chemistry, especially important for turbocharged engines.

PERFORMANCE FEATURES

- suitable to use for the following specifications: API SQ/SP/SN Plus, ACEA C5 / C6 (only for 0w20), VW 508.00 / 509.00 (only for 0w20), MB 229.71, Opel OV 040 1547-A20, Dexos D, Ford WSS-M2C952-A1, STJLR.03.5006, ILSAC GF-7A, Chrysler MS-12145, Honda, Hyundai, Infiniti, Kia, Lexus, Nissan, Suzuki, Toyota and other types of vehicles whose manufacturers recommend an oil with this classification.

APPLICATION

- designed for modern Diesel, gasoline and hybrid passenger cars;
- MID SAPS level and balanced detergent package for protection against LSPI;
- high-quality dispersion technology to ensure engine cleanliness at high and low temperatures.

PROPERTIES

Viscosity grade SAE	0W20	5W20
Density at 15°C [kg/m ³], max	870	870
Kinematic Viscosity at 100°C [mm ² /s]	6.9 - 9.3	6.9 - 9.3
Dinamic Viscosity at -30°C [cP], max		6600
-35°C [cP], max	6200	
Viscosity Index	160	160
Flash Point [°C]	210	210
Pour Point [°C]	-43	-40
Color	green	green

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg	☒ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☒ 208l	☒ 1000l
☒ 4l	☒ 5l	☒ 10l	☒ 20l	☒ 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.