



HEXOL SYNLIN SPRINT SAE 10W30 – 10W40 MOTOR OIL

PRODUCT DESCRIPTION

HEXOL Synline Sprint is a high-quality, multigrade, synthetic blend oil, formulated from synthetic and mineral base oils and a package of additives with anti-corrosion, antioxidant, anti-wear, anti-foaming properties, recommended for year-round use in naturally aspirated or turbocharged gasoline, gas or diesel engines. The oil is compatible with E85 regulations regarding fuels with an ethanol content of 85%.

PERFORMANCE FEATURES

- can be used for the specifications: API Service SL/CF-4, ACEA A2/B3, VW 500.00, 501.01, 505.00, MB 229.1, Renault 0700, FORD WS-M2, PSA B71 2294, B71 2300, FIAT 9.55535-H2, JASO MA-2 and other types of vehicles whose manufacturers recommend an oil with this classification;
- protects the engine by controlling and minimizing varnish, resin, rust deposits;
- contains anti-wear, anti-corrosion and anti-foaming additives that extend the life of the engine ensuring its optimal operation;
- high viscosity index that allows for optimal thermal stability.

APPLICATION

- can be used in cars and vans with gasoline, gas or diesel engines where the manufacturer recommends using an oil with the performances mentioned above;
- the change interval is that indicated by the engine manufacturer.

PROPERTIES

Viscosity grade SAE	10W30	10W40
API Service	SL/CF-4	SL/CF-4
Density at 15°C [kg/m ³], max	880	880
Kinematic Viscosity at 100°C [mm ² /s]	9.3 – 12.5	12.5 - 16.3
Dinamic Viscosity at -25°C [cP], max	7000	7000
Viscosity Index	150	150
Flash Point [°C]	210	210
Pour Point [°C]	-38	-37

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg	☒ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☒ 208l	☒ 1000l
☒ 4l	☒ 5l	☒ 10l	☒ 20l	☒ 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.