



HEXOL SYNLINER SUPERDIESEL 5W30 MOTOR OIL

PRODUCT DESCRIPTION

HEXOL Synliner Superdiesel 5W30 is a high-performance, "MID SAPS" synthetic engine oil. Made from synthetic base oils and an additive package, it provides excellent flow and lubrication characteristics.

PERFORMANCE FEATURES

- can be used for specifications: ACEA C2/C3, API service CF/SN and CF/SM, VW 502.00, 505.00, 505.01, MB 229.51, PSA B71 2290, Porsche C30, Renault RN 017, Fiat 9.55535-S2, JASO DL-1 and other types of vehicles whose manufacturers recommend this classification;
- MID SAPS technology, suitable for vehicles equipped with DPF, EGR or SCR.

APPLICATION

- suitable for cars, vans and light commercial vehicles equipped with naturally aspirated or turbocharged diesel or gasoline engines, equipped with or without particulate filter (DPF) or three-way catalysts, where the manufacturer recommends an oil with the performance mentioned above;
- the change interval will be according to the engine manufacturer's instructions.

PROPERTIES

Viscosity grade SAE	5W30
Density at 15°C [kg/m ³], max	870
Kinematic Viscosity at 100°C [mm ² /s]	9.3 – 12.5
Dinamic Viscosity at -30°C [cP], max	6600
Viscosity Index	150
Flash Point [°C]	220
Pour Point [°C]	-38

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg		
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☒ 1l	☐ 3l
☒ 4l	☒ 5l	☒ 10l	☒ 20l	☒ 60l	☒ 208l	☒ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products