



HEXOL TBA 32 – TBA 46 – TBA 68

TURBINE OIL

PRODUCT DESCRIPTION

HEXOL TBA 32 – TBA 46 – TBA 68 are oils specially formulated for turbine lubrication, produced with a high quality level and based on a special formulation of refined mineral oils with a high degree of stability and a special additive package, without zinc.

PERFORMANCE FEATURES

- can be used for specifications DIN 51515-1(L-TD), DIN 51515-2(L-TG), ISO 6743-5, ISO-L-TSA, ISO-L-TGA, AIST 120, BS 489, GE GEK 32568 A/C, CEGB 207001, Mitsubishi Heavy Industries E00-87182, TLV 9013;
- provides excellent protection;
- contains special corrosion protection additives;
- contains antifoam additives.

APPLICATION

- recommended for most types of turbines;
- can also be used in compressors, hydraulic systems, for general lubrication of machine components where a specific type of lubricant is not recommended, light gears, couplings, axles, raceways.

PROPERTIES

Viscosity Grade ISO	32	46	68
Density at 15°C [kg/m ³], max	890	895	895
Kinematic Viscosity at 40°C [mm ² /s]	28.8 – 35.2	41.4 – 50.6	61.2 – 74.8
Flash Point [°C]	205	210	220
Pour Point [°C]	-36	-33	-30

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg		
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 1l	☐ 3l
☐ 4l	☐ 5l	☒ 10l	☒ 20l	☒ 60l	☒ 208l	☒ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.