



HEXOL TURBODIESEL 10W40 – 15W40

MOTOR OIL

PRODUCT DESCRIPTION

HEXOL Turbodiesel is a high-quality, multigrade mineral oil recommended for use in all seasons, especially in diesel engines, but also for gasoline or gas engines, naturally aspirated or turbocharged.

Formulated from mineral base oils, high-performance additives, it ensures excellent engine protection.

PERFORMANCE FEATURES

- can be used for the specifications: API CF-4/CF/SJ, ACEA A2/B3, ACEA E2, MB 228.1, MAN 271, MTU 1.0, MACK EO-K/2, VOLVO VDS, VW 505.00 and other types of vehicles whose manufacturers recommend this classification;
- contains anti-wear, anti-corrosive, anti-foaming additives, which extend the life of the engine ensuring optimal operation;
- ensures lubrication, cooling and protection of engines operating at high temperatures;
- controls and minimizes deposits and sediments of varnish, rust, carbon, etc.

APPLICATION

- cars, vans and equipment with diesel, petrol or gas engines, with natural or turbo aspirated, subject to intensive use;
- the replacement interval is that indicated by the engine manufacturer.

PROPERTIES

Viscosity grade SAE	10W40	15W40
API Service	CF-4/CF/SJ	CF-4/CF/SJ
Density at 15°C [kg/m ³], max	880	885
Kinematic Viscosity at 100°C [mm ² /s]	12.5 – 16.3	12.5 – 16.3
Dinamic Viscosity at -20°C [cP], max		7000
-25°C [cP], max	7000	
Viscosity Index	135	125
Flash Point [°C]	220	220
Pour Point [°C]	-33	-27

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg	☒ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☒ 208l	☒ 1000l
☒ 4l	☒ 5l	☒ 10l	☒ 20l	☒ 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.

HEXOL®

HEXOL LUBE SRL

Zona Metropolitană Oradea • 417166 Paleu, Str. Ardealului nr. 1A, jud. Bihor • România
Telefon +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com