



HEXOL LI EP2 SUPREME

GREASE

PRODUCT DESCRIPTION

HEXOL LI EP2 Supreme is a high-performance, high-quality, water-resistant lithium soap-based universal grease for use in a wide range of applications such as automation, agriculture or industry. It provides high-performance lubrication in working conditions ranging from -30 °C to +140 °C. Formulated from high-quality mineral oil and lithium soap, it withstands extreme pressure conditions, containing EP, anti-corrosion, anti-wear and antioxidant additives.

PERFORMANCE FEATURES

- can be used for specifications: ISO 6743-9: L-XCCEB 2, NLGI-2, DIN 51502: KP2K-30;
- water resistant;
- protects against corrosion;
- does not contain toxic components.

APPLICATION

- it is recommended for lubricating bearings and raceways subjected to high loads and high temperatures, found in the automotive, metallurgical and construction industries.

PROPERTIES

Appearance	Green, homogeneous
Dropping point [°C], min	195
Penetration after 60 Strokes at 25°C(0.1mm)	265-295
Corrosion at 100 °C / 24 h (steel)	passed

PACKAGING

☒ 0.4kg	☒ 1kg	☒ 4kg	☒ 15kg	☒ 180kg	☐ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 208l	☐ 1000l
☐ 4l	☐ 5l	☐ 10l	☐ 20l	☐ 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.