



HEXOL H 68 – H 100

HIDRAULIC OIL

PRODUCT DESCRIPTION

HEXOL H are standard quality hydraulic oils specially formulated for use in industrial, construction, mining, pick-up hydraulic equipments as well as in any other fixed and mobile hydraulic systems. Hexol H oils are produced from highly refined mineral base oils.

PERFORMANCE FEATURES

- can be used for ISO 11158 HH, ISO-L-HH, DIN-H specifications;
- low foaming;
- provides good lubrication;
- remain stable even under conditions of exposure to moisture and extreme temperatures.

APPLICATION

- in all fixed and mobile industrial hydraulic systems for which the manufacturer recommends a lubricant with these technical specifications.

PROPERTIES

Viscosity Grade SAE	68	100
Density at 15°C [kg/m ³], max	885	895
Kinematic Viscosity at 40°C [mm ² /s]	61.2-74.8	90-110
Flash Point [°C]	220	230
Pour Point [°C]	-12	-12

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg		
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 1l	☐ 3l
☐ 4l	☐ 5l	☒ 10l	☒ 20l	☐ 60l	☒ 208l	☒ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.