



HEXOL LI3 STANDARD

GREASE

PRODUCT DESCRIPTION

HEXOL LI3 Standard is a general purpose grease with good mechanical stability and water resistance ensuring good lubrication and protection. This grease is produced from highly refined base oils, lithium soaps and a complex additive package that provides anti-corrosion, anti-oxidation and anti-wear protection. This product can be used with excellent results in the temperature range between -25 °C and +140 °C.

PERFORMANCE FEATURES

- can be used for specifications: ISO 6743-9: L-XBCEA 3, NLGI-3, DIN 51502: K3K-25;
- has good water resistance;
- maintains low friction;
- provides good corrosion protection;
- has good mechanical stability.

APPLICATION

- general purpose grease for automotive, agricultural and industrial applications;
- recommended for the lubrication of bearings and bearings operating at medium speeds and loads;
- can be used in centralized lubrication systems where a grease of NLGI-3 consistency is recommended.

PROPERTIES

Appearance	Brown, homogeneous
Dropping point [°C], min	195
Penetration after 60 Strokes at 25°C(0.1mm)	220-250
Corrosion at 100 °C / 24 h (steel)	passed

PACKAGING

☒ 0.4kg	☒ 1kg	☒ 4kg	☒ 15kg	☒ 180kg	☐ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 208l	☐ 1000l
☐ 4l	☐ 5l	☐ 10l	☐ 20l	☐ 60l		

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.