



HEXOL SYNLINE TORSION PSF/CHF

POWER STEERING AND CENTRAL HYDRAULIC FLUID

PRODUCT DESCRIPTION

HEXOL Synline Torsion PSF/CHF is a high-quality synthetic power steering and central hydraulic fluid. The high performance additive package ensures optimal temperature stability, high oxidation stability, excellent cold properties and high shear stability.

PERFORMANCE FEATURES

- Suitable to use for: ISO 7308, DIN 51524 Teil 3, BMW 83 29 0 429 576, Ford M2C204-A2, VW TL 521 46, MB 345.0 and others types of vehicles whose manufacturers recommend this type of oil;
- ensures long life for components subject to wear;
- excellent oxidative stability, ensuring protection against corrosion;
- very good anti-foaming behavior.

APPLICATION

- Suitable to use in vehicles for the following applications: power steering and central hydraulic systems, hydraulic convertible top control, shock absorbers, central locking, level control and in any other application where manufacturers recommend this type of oil.

PROPERTIES

Density at 15°C [kg/m ³], max	860
Kinematic Viscosity at 100°C [mm ² /s]	7 – 12.5
Viscosity Index	200
Flash Point [°C]	210
Pour Point [°C]	-45
Brookfield Viscosity at -40°C [mPa.s]	20000
Colour	GREEN

PACKAGING

☐ 0.4kg	☐ 1kg	☐ 4kg	☐ 15kg	☐ 180kg	☐ 1l	☐ 3l
☐ 0.23l	☐ 0.45l	☐ 0.5l	☐ 0.6l	☐ 0.9l	☐ 2l	☐ 1000l
☐ 4l	☒ 5l	☒ 10l	☒ 20l	☒ 60l	☒ 208l	☒ 1000l

Details concerning the products are of indicative nature only, they do not constitute an offer or legally binding. Data in tables are typical values obtained at standard tolerance of production lot and there are possible differences due to continuous product development and batch differences. Actual parameters are specified in quality and conformity certificates of each batch of products.

HEXOL LUBE SRL

Zona Metropolitană Oradea • 417166 Paleu, Str. Ardealului nr. 1A, jud. Bihor • România
Telefon +40 259 454216 +40 259 449203 +40 724 322992 Fax +40 259 428299 e-mail: oradea@hexol.com